

Miniature external cavity laser with 100 kHz linewidth





## **miniECL**

Single Frequency Laser Diode 80 mW @ 770 nm (K D1 line), @ 780 nm (Rb D2 line) @ 852 nm (Cs D2 line), @ 895 nm (Cs D1 line)

### PRODUCT HIGHLIGHTS

- + Small linewidth of 100 kHz
- + Very good SMSR (typ. 50 dB)
- + Integrated beam collimation
- + Thermal management by integrated thermoelectric cooler and thermistor

#### Datasheet:

EYP-ECL-0770-00080-1500-BFW01-0005 EYP-ECL-0780-00080-1500-BFW01-0005 EYP-ECL-0852-00080-1500-BFW01-0005 EYP-ECL-0895-00080-1500-BFW01-0005

# ONE OF OUR NEWEST INNOVATIONS

With the launch of the *miniECL* TOPTICA EAGLEYARD continues its ambitious path and introduces another game-changing innovation to the market. This single frequency laser diode has a super fine linewidth of typical 100 kHz. A stable performance is ensured by the integrated cavity in the robust butterfly package. Moreover, wavelengths between 650 – 1100 nm are customizable upon request, opening more freedom across the spectrum.

## YOUR ADVANTAGES

- Ease of use thanks to high integration level
- Robustness due to hermetically sealed butterfly package
- Very small linewidth for precise results
- ✓ Possibility of wavelength customization



### Contact us!

eagleyard Photonics GmbH Rudower Chaussee 29 | 12489 Berlin, Germany Tel.: +49 30 6392 4520 | Fax: +49 30 6392 4529 E-Mail: info@toptica-eagleyard.com | www.toptica-eagleyard.com

